

EP02 - PU Foam Ear Plugs (200 Pairs)

Collection: Ear Plugs

Range: Hearing Protection

Materials: Mesh with PU Foam

Outer Carton: 10

Product information

PU foam disposable ear plugs made with soft and durable foam. Easy to insert and remove. Excellent attenuation level and a comfortable fit for long periods of use. Each pair comes inside an individual hygienic polybag with fitting instructions.



Hearing Protection

Hearing problems occur when you are exposed to hazardous working conditions without wearing the correct protective equipment.

Standards

EN 352-2 (SNR 33dB)

ANSI S3.19 (NRR 32dB)

AS/NZS 1270 (SLC(80) 19dB - Class 3)

Features

- Disposable ear plugs made from soft PU foam
- Tapered shape for easy insertion and removal
- Supplied in a handy portable dispenser box
- One pair per polybag for hygienic storage
- Excellent attenuation rate
- Unit of sale is 200 pairs
- Retail box which aids presentation for retail sales
- Individually packed for vending machines
- CE certified
- CE-CAT III



PRODUCT SPECIFICATION & TECHNICAL DATA

EP02 - PU Foam Ear Plugs (200 Pairs)

Commodity Code: 3926909790

Test House

ALIENOR CERTIFICATION (Notified Body No.: 2754)

ZA du Sanital

86100, France

Cert No: 2754/1246/159/06/18/0288

SATRA Technology Centre Ltd (Notified Body No.: AB: 0321)

SATRA Technology Park

NN16 8SD, United Kingdom

Michael & Associates, Inc. (Notified Body No.:)

2766 W. College Ave Suite 1

PA 16801, United States

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	DUN14
EP02ORR	Orange	60.0	35.0	33.0	0.4580	0.0693	5036108171941	15036108622365

PERFORMANCES - SOUND ATTENUATION - EN352-2:2002

EP02/EP08/EP30

A	Frequency (Hz)	125	250	500	1000	2000	4000	8000
B	Means Attenuation (dB)	36.5	34.2	39.1	37.8	39.6	44.9	46.2
C	Standard Deviation (dB)	4.7	4.5	4.8	5.8	4.0	6.4	6.2
D	Assumed Protection (dB)	31.7	29.7	34.2	32.0	35.5	38.5	40.1

SNR = 36 dB H = 36 dB / M = 33 dB / L = 32 dB

PERFORMANCES - SOUND ATTENUATION ANSI S.19-1974

Tested by Michael & Associates, Inc. – 400 Long Lane, PA Furnace, PA 16865, USA

EP02/EP08

A	Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000
B	Means Attenuation (dB)	39.8	40.4	42.6	40.3	39.1	45.2	45.7	48.3	47.4
C	Standard Deviation (dB)	3.0	3.9	2.9	3.6	3.7	3.0	2.5	4.9	3.7

NRR (Noise Reduction Rating) = 32 dB

EP02ORR